



Designed to work with central heating radiator systems as standard



Designed to work with piped underfloor heating systems as standard



Use for domestic hot water systems by adding an indirect hot water storage cylinder

Technical data

Voltage 230V / 400 50Hz

IEC Protection Class I

IP Rating IP22

Efficiency class **D**

Max temp 80°C

Max pressure 3 bar

Warranty 3 years

Electric Flow Boiler with Pump

The new ThermoSphere electric boiler range. The perfect electric water heating solution for homes without gas supply or where space is at a premium

ThermoSphere electric flow boilers with pump provide heating for wet central heating systems and underfloor heating. Suitable for open vented or pressurised systems. No flue requirement.

Compact and unobtrusive, ideal for storage cupboards, extensions, loft conversions and garages where space is challenge.

Works with standard central heating radiators, wet underfloor heating manifolds, programmers, room thermostats and thermostatic radiator valves.

Outputs range from 1.5kW to 24.0kW and each boiler features 3 heating elements that can be switched independently.

Compliant with EcoDesign directive 2009/125/EU, Regulation (EU) 811/2013, Regulation (EU) 813/2013.

Packed with energy saving features

- Controllable, efficient central heating
- Integrated pump set and pressure release valve
- Works with standard radiators, programmers, room thermostats and thermostatic radiator valves
- Works with water underfloor heating systems
- Suitable for pressurised or open vented systems
- Domestic hot water in conjunction with indirect cylinder
- No flue or fuel tanks means flexible installation
- Up to 99.8% efficient and EcoDesign Lot20 compliant
- Compact and lightweight for easy installation
- Minimal service and maintenance costs

Feature	TSEFB-P4.5	TSEFB-P6	TSEFB-P9	TSEFB-P12	TSEFB-P15	TSEFB-P18	TSEFB-P24
Max output (Kw)	4.5	6.0	9.0	12.0	15.0	18.0	24.0
Output per element	1.5	2.0	3.0	4.0	5.0	9.0	9 + 15
No. of elements	3	3	3	3	3	2	2
Pump included	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Voltage	230 / 400	230 / 400	230 / 400	230 / 400	400	400	400
Max Current (A)	21	27	40	53	22	26	35
Working pressure (MPa)	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Working pressure (BAR)	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Working pressure (PSI)	29	29	29	29	29	29	29
Max working Temperature (°C)	80	80	80	80	80	80	80
Cable section (mm ²)	4	4	4	4	4	4	4
Weight (Kg)	14	14	14	14	14	22	22
Height (mm)	755	755	755	755	755	755	755
Width (mm)	255	255	255	255	255	355	355
Depth (mm)	150	150	150	150	150	150	150
Energy efficiency class	D	D	D	D	D	D	D
Warranty duration	3 years	3 years	3 years	3 years	3 years	3 years	3 years